




Bezeichnung	A	C max.	LF1	LF2	CH js16	CN	AX	KK	EU	EN	B	Z	Zylinderschraube mit Innensechskant	Ma (Nm)	Gewicht (kg)
KM-20-U	41	56	25	28	50	20	17	M16x1,5	16	19	25	9°		32	
KM-25-U	41	56	25	28	50	25	17	M16x1,5	20	23	25	7°		32	
KM-30-U	46	64	30	32	60	30	23	M22x1,5	22	28	32	6°		32	
KM-35-U	66	78	40	42	70	35	29	M28x1,5	25	30	40	7°	M10x25	40	1,2
KM-40-U	78	94	45	50	85	40	36	M35x1,5	28	35	49	7°	M12x30	80	2,0
KM-50-U	90	116	55	63	105	50	46	M45x1,5	35	40	61	7°	M12x30	80	3,8
KM-60-U	108	130	65	70	130	60	59	M58x1,5	44	50	75	7°	M16x40	160	5,4
KM-70-U	130	154	75	82	150	70	66	M65x1,5	49	55	86	6°	M16x40	160	8,5
KM-80-U	152	176	80	95	170	80	81	M80x2	55	60	104	6°	M20x50	300	12,0
KM-90-U	162	206	90	113	210	90	101	M100x2	60	65	124	5°	M20x50	300	21,5
KM-100-U	172	230	105	125	235	100	111	M110x2	70	70	138	7°	M20x50	300	27,5
KM-110-U	194	265	115	142,5	265	110	125	M120x3	70	80	152	6°	M24x60	500	40,5
KM-120-U	224	340	140	180	310	120	135	M130x3	85	90	172	6°	M30x80	1000	76,0